

Server Lifters

The range of server lifters from **ODC** Europe are designed to tackle the challenges of manoeuvring IT equipment around the data centre environment. Unlike the more traditional bulky server lifting alternatives, our range of server lifters are both lightweight and portable and easy to operate.

Battery Operated Server Lifters

The **ODC** battery operated server lifter is manufactured using lightweight aluminium and rigid steel and finished with a two part epoxy resin coat. All models include sealed-for-life, maintenance free 24 volt batteries and an integral auto cut-off charger. Operation is via a push button controller that can be hand held or used from its handle-mounted holster.

Features & Benefits

- Models are available with standard height or extending masts for extra reach.
- Dual speed elevation and descent for controlled lifting.
- Attractive design with soft grip bull bar handles.
- Battery charge meter.
- Stainless steel bearings are fitted in the four non-marking all-swivelling wheels, rear wheels all have total stop brakes.
- Trip mechanism prevents descending lift lowering onto any obstacle.
- Provides greater protection to equipment and operators during installation process.
- Available in a choice of lifting capacities that includes: 65Kg, 85Kg, 105Kg, 155Kg and 205Kg.
- Maximum height reach of 1760mm (40U) on the 80Kg extended mast model (49-SL-85EM).
- Most available from stock for short leadtime.



Part Number	Weight Capacity*	Lowered Height	Raised Height	Platform (WxD)	Weight
49-SL-65	65Kg	125mm	1440mm (32U)	470mm x 410mm	39Kg
49-SL-85	85Kg	125mm	1440mm (32U)	600mm x 470mm	39Kg
49-SL-85EM	80Kg	125mm	1760mm (39U)	600mm x 470mm	42Kg
49-SL-105	105Kg	130mm	1345mm (30U)	600mm x 470mm	42Kg
49-SL-105EM	100Kg	130mm	1655mm (37U)	600mm x 470mm	45Kg
49-SL-155	155Kg	130mm	1345mm (30U)	600mm x 470mm	43Kg
49-SL-155EM	150Kg	130mm	1655mm (37U)	600mm x 470mm	45Kg
49-SL-205	205Kg	105mm	1320mm (29U)	560mm x 600mm	64Kg
49-SL-250	250Kg	105mm	1320mm (29U)	560mm x 600mm	105Kg

Telescopic Mast Server Lifter

The Battery Operated 49-WP205 is also available with telescopic mast to provide higher positioning of equipment, whilst making it easier to navigate through doorways or aisle containment systems.

Part Number	Weight Capacity*	Lowered Height	Raised Height	Platform (WxD)
49-SL-205TELE	100Kg	105mm	2464mm (55U)	600mm x 470mm



Manual Server Lifters

The EDP manually operated server lifters provide a cost effective, maintenance free solution to moving and positioning IT equipment.



Features & Benefits

- Three weight capacity models available: 85Kg, 140Kg and 200Kg.
- Available in powder coated mild steel as standard or optional stainless steel.
- "Easy Winch" system is used to raise and lower the load safely with the minimum of manual effort.
- Automatic braking function prevents uncontrolled lowering.
- Lifts are remarkably manoeuvrable and extremely lightweight.
- All four wheels swivel and two are fitted with total stop brakes complete with toe guards.
- High level stability and durability.

Part Number	Weight Capacity*	Lowered Height	Raised Height	Platform (WxD)	Weight
49-WPM-85	85Kg	140mm	1560mm (35U)	600mm x 470mm	34Kg
49-WPM-140	140Kg	130mm	1605mm (36U)	600mm x 500mm	45Kg
49-WPM-200	200Kg	130mm	1430mm (32U)	600mm x 500mm	55Kg

* Weight Capacities are based on a load centre of 235mm from edge of platform closest to mast. If load is longer than platform the weight capacity will be reduced.